

DFMD – Multi Zone

AIDF-901

- ✓ Double infrared detector, digital circuit design, anti-interference.
- ✓ Adjustable sensitivity can be adjusted from 0 to 100 as per the required inferences such as the adjustment to avoid the coins, keys, buckle, etc.
- ✓ The function of statistics: show the number of passed examinees and the alarm times.
- ✓ Easy to operate: the operation panel is covered by thin plastic, Bright light alarm can be shown in the warning zones directly and find the precise position of the target metal.
- ✓ Both light and auditory alarms can make the warning clear, and improves work efficiency.
- ✓ No harm to people: The gate is harmless to people with cardiac pacemakers, pregnant women, tapes, videotapes, etc.
- ✓ Convenient installation: Integrated design, you can assemble or disassemble it in 20 minutes with the operation instruction.

Power Supply	220-260V/AC
Power Output	10 W
Passage Dimension	2220mm(H) x820mm(W)x500mm(D)
Work Environment	-20 °C to +45 °C
Counter Module	Yes IN/OUT
Through Put Rate	<30
Battery Backup	Optional
Max Distance	0.3m at low sensitivity;0.5m at high sensitivity
Indicator Light	One green indicator
Alarm In/Out	1 Output
Network	PC Connectivity (Optional)
Operation Power	12V DC

